Engineered flooring: E&K offers all of its flooring as both engineered and solid.

Planed Douglas Fir Flooring

Product Name: Planed Douglas Fir Flooring plus name of the stain.

Species: Domestically sourced Reclaimed Douglas Fir.

Source: Old structures including barns, factories and residences that are deconstructed.

Color: Natural color of Planed Douglas Fir or custom stain.

Grade: Reclaimed wood is not officially graded. All material supplied is hand checked for usability. Holes and surface checks will be filled. There will be very little sap wood. Generally, there is a range from select grade to rustic grade. Certain floors are designed to be more rustic and others more refined.



Dimensions Solid: Thickness: 5/8 or 3/4", Width: 3"–9"+, wider widths upon request, Length 2'–8'+ (with most boards between 4 - 8') is standard, upon request we can accommodate custom lengths.

Dimensions Engineered: Same as solid. Wear layer either 4mm or 6mm.

Milling: Tongue and groove. Relief on back of boards. If Unfinished, then square edge. If Pre-finished, then planks will have a Micro-bevel.

Finish: We have a wide range of custom finished products and in some cases create custom finishes for our clients.

Moisture Content: Flooring is kiln dried to 6–9% prior to milling. Material is kept in a stable moisture environment while being processed. For shipping all flooring is wrapped to keep moisture levels stable during transit.

Surface: Boards are planed and sanded, resulting in a surface that is smooth and soft to the touch. Certain products may include wire brushing which creates a more rustic look. There will be no boards that present any type of splintering. Every board is checked by hand to insure its usability. Planed wood does not include saw marks. There may be present nail holes and surface checks that do not effect the integrity of the plank, both of these items will be filled with a suitable filler unless requested leave voids as is. There may be some evidence of insect marks which generally are in the form of pin holes. Knots will be present in varying sizes on some boards. There will not be an abundance of knots but some boards will have more knots and some none at all. All knots present will be sound knots. Chipped or damaged knots will either be patched or cut out. Grain pattern will be mixed and may include some quarter sawn, plain sawn and rift sawn grain patterns. There will be very little sap wood present.

Installation, Handling, and Storing: We recommend that installation, handling, storing, prep of job site all follow the guidelines established by the National Wood Flooring Association (www.nwfa.org). If you are not a member, we can supply technical guidelines upon request.

Overage: We recommend 5–10% overage depending on the amount of cuts necessary and depending on the need to have extra material to be able to reject certain boards for color.

Additional: If you have additional questions regarding any of the above or other items related to our floors, please contact us.





Planed Douglas Fir Flooring

Our reclaimed Planed Douglas Fir flooring showcases the natural beauty of the planks, featuring a smooth surface that highlights the wavy grain patterns and unique characteristics of each board. Douglas Fir is a classic West Coast species that makes this reclaimed wood flooring stand out for its authentic look and feel.

Species:	Douglas Fir
Thickness:	5/8″ or 3/4″
Widths:	3″, 5″, 6 1/2″, 8 1/2″, Random 3″–9″, Random 5″–9″
Lengths:	2′–8′+
Milling:	Tongue and Groove, Relief in back, Microbevel
Surface:	Planed (Wire Brush Option)
Finish:	Oil and Water Based
Type:	Engineered or Solid

Sample Finishes

Alpine (FL654)

Ashfield (FL646)

Preston (FL354)

E&K Vintage Wood | ekvintagewood.com | info@eandkwood.com
1308 W El Segundo Blvd | Gardena, CA 90247 | (310)-306-6900

nwfa National Wood Flooring Association